

PI
a grain moisture analyzer assembly mounted ex-situ on said external wall of said combine; and

9
means for bypassing a portion of the grain passing through said moving means through said grain moisture analyzer [.] including an inlet opening and an outlet opening formed in said external wall of said combine for supplying and exhausting grain to and from said grain moisture analyzer;

PI
a sensing cell for measuring grain moisture; and

feed means for moving the grain from said sensing cell to said outlet opening formed in said external wall for returning said portion of grain back into a normal flow of moving grain within the combine thresher.

2
4. (Amended) A combine as set forth in claim [3] 1 including means for determining the grain moisture content when said sensing cell is filled with grain and establishing a control signal indicative thereof.

7
9. (Amended) A continuous grain moisture analyzer assembly suitable for ex-situ mounting on an external surface of a combine harvester providing access to grain therein comprising;

PI
a sensing cell for measuring the moisture of grain filling said cell;
detector means for sensing the full condition of said sensing cell and establishing a control signal indicative thereof; [and]

PI
flow means for moving grain from said sensing cell in response to the control signal from said detector means [.] ; and

PI
wherein said sensing cell includes an impedance cell having a plurality of plates to increase the measuring sensitivity of the moisture analyzer and with the external two plates being ground plates to reduce EMI and RFI interference thereby.

10
12. (Amended) A grain analyzer as set forth in claim 11 wherein said operator interface module includes a first microprocessor connected to said [cell dual] detector means to actuate said flow means in response to said control signal from said detector means.

14
16. (Amended) A method of providing continuous grain moisture readings of the grain being harvested to a combine harvester operator comprising the steps of:
passing a portion of the grain being harvested from the combine to a moisture analyzer sensing cell mounted ex-situ of the combine;
filling said sensing cell with passed grain; [and]
actuating the passing of the grain from the sensor cell back to the combine to provide a continuous bypass of grain from the combine through the sensor cell and continuous moisture measurement thereby[.] ; and

PI
automatically setting the frequency of the cell voltage to an optimum frequency for detecting the broadest range of moisture sensed by the cell.

15
17. (Amended) A method as set forth in claim 16 including the further calculating
step of averaging of continuous grain moisture measurements over an operator
determined period.

14
24. (Amended) A grain moisture analyzing assembly as set forth in claim [23] ~~9~~
wherein said plurality of plates is five plates with two central readout plates and three
ground plates forming four separate measuring chambers.

waive
JDW
09/26/96
7/2/01
Claim 30, line 1 change "29" to ----- 16 -----.

can be waived
Claim 32, line 2 after "frequency" insert ----- f^* via the known standard
relationship $f^* = 1/t$ -----.

Add new claims 33 and 34 as follows:

29
33. A continuous grain moisture analyzer assembly suitable for ex-situ mounting on
an external surface of a combine harvester providing access to grain therein
comprising;

PI
L
PI
PI
a sensing cell for measuring the moisture of grain filling said cell;
detector means for sensing the full condition of said sensing cell and
establishing a control signal indicative thereof;
flow means for moving grain from said sensing cell in response to the control
signal from said detector means; and
an operator interface module for controlling said analyzer assembly in response
to operator inputs and control signals from said analyzer assembly.

30
34. A method of providing continuous grain moisture readings of the grain being
harvested to a combine harvester operator comprising the steps of;
passing a portion of the grain being harvested from the combine to a moisture
analyzer sensing cell mounted ex-situ of the combine;
filling said sensing cell with the passed grain;
actuating the passing of the grain from the sensor cell back to the combine to
provide a continuous bypass of grain from the combine through the sensor cell and
continuous moist measurement thereby; and
PI
L
PI
passing the portion of the grain to a sensing cell formed from an impedance
moisture measuring cell having a plurality of plates for increased measurement
sensitivity.

REMARKS